

New York Independent System Operator, Inc.
FERC Electric Tariff
Original Volume No. 2
Attachment D

ATTACHMENT D

DATA REQUIREMENTS FOR INTERNAL GENERATORS FOR LBMP BIDDERS

- TABLE D-1: Data Requirements for Internal Generators for ~~LBMP Bidders~~**
- TABLE D-1a: Data Requirements for Demand Side Resources for ~~LBMP Bidders~~**
- TABLE D-2: Data Requirements for External Generators for ~~LBMP Bidders~~**
- TABLE D-3: Data Requirements for Generator Commitment Bids for ~~LBMP Bidders~~**
- TABLE D-3a: Data Requirements for Demand Side Resource Commitment Bids for ~~LBMP Bidders~~**
- TABLE D-4: Data Requirements for Generator Energy Bids**
- TABLE D-4a: Data Requirements for Demand Reduction Bids**
- TABLE D-5: Data Requirements for Generator Regulation ~~(and Frequency Control)~~ Service
Bids**
- TABLE D-6: Data Requirements for Generator and Demand Side Resource Operating
Reserve Bids**
- TABLE D-7: Data Requirements for Virtual Transaction Bids to Purchase Energy**
- TABLE D-7.1: Data Requirements for Virtual Transaction Bids to Supply Energy**
- ~~TABLE D-8: Data Requirements for Interruptible Load Spinning Reserve Bids~~**

Issued by: William J. Museler, President
Issued on: September 4, 2001

Effective: October 30, 2001

Attachment D
Table D-1
Data Requirements for Internal Generators for LBMP Bidders

Data Item	Cat.	Bid Parameters	Variability	Comments
Company Name	G	--	Static Required	Parent Organization.
Generator Name/No.	G	--	Static Required	
Generator Unit Code/ID	G	--	Static Required	Unique code which identifies the Generator to the ISO.
Bus	G	Bus No.	Static Required	Specific location of Generator within the NYCA.
Submitted By	G	Name	May vary Required	Organization submitting Bid. Multiple organization can be authorized to submit Bids with the ISO accepting the most recent. A single organization must be specified to receive to receive invoices from the ISO.
DMNC (Summer & Winter)	P/G	MW	Static Required	Dependable Maximum Net Capability. Confirmed by test for units <u>Generator's</u> with installed <u>Installed</u> Capacity contracts, or historical production data.
Power Factor	P/G	MW/MVA	Static Optional	Generator's tested Power Factor for producing Reactive Power (MVARs) at normal high operating limit MW output level. Provided, provided it is at least 90% of DMNC. This is required for Generators receiving Voltage Support Payments.
Installed Capacity Contracts	G	MW	May vary Required	Installed Capacity contracts in effect with LSEs within the NYCA. The ISO may limit maximum and/or minimum amounts of Installed Capacity by location due to reliability Constraints.
<u>Normal Upper Operating Limit</u>	<u>C/D</u>	<u>MW</u>	<u>May change Required by hour for Day-Ahead</u>	<u>Maximum output of a unit Generator that could be expected in any hour of the following operating day. The ISO must be informed of a limit change that results in less capability.</u> <u>Capability.</u>
<u>Emergency Upper Operating Limit</u>	<u>C/D</u>	<u>MW</u>	<u>May change Required by hour for Day-Ahead</u>	<u>Maximum output that a Generator's owner expects it can reach during extraordinary conditions. A Generator's Emergency Upper Operating Limit may be no less than its Normal Upper Operating Limit.</u>
Normal Response Rate (NRR)	P/C/D	MW/min.	May vary Required	To be provided as an expected response rate for SCD. <u>Generators may specify up to three NRRs.</u> The minimum acceptable response rate is 1% of a unit <u>Generator's</u> gross output per minute.
Regulation Response Rate (RRR)	P/C/D	MW/Min.	Same as Optional NRR	To be provided as an expected response for regulation <u>Regulation Service.</u> If RRR differs from NRR, the total expected response rate is restricted to the maximum of the two rates.
Emergency Response Rate (ERR)	P/C/D	MW/Min. or <u>Piecewise linear curve with MW Output as independent variable and MW/Min. as dependent variable</u>	Same as <u>Optional</u> NRR	To be provided as expected response for reserve pickups; <u>A Generator's ERR must at least be greater than or equal to the capacity-weighted average of its NRRs, NRR.</u> If ERR is reduced, then unit will be subject to a performance penalty if called upon. <u>ERR for Class B Reserve bidders must at least equal the static NRR from Pre-Qualification data.</u> <u>Bidders must inform ISO of all changes to ERR.</u>
Reactive Power Capability	P/G	Piecewise linear curve with MW as independent variable and +/- MVARs as dependent variable	Static Optional	Update as changed.
<u>Physical Minimum Generation Limit</u>	<u>P/G</u>	<u>MW</u>	<u>Static Required</u>	

Notes:

Internal Generators LBMP bidders are located within the NYCA.
 Cat. = Data Categories: **G** = General; **P** = Pre-Qualification; **C** = Commitment; **B** = Balancing; **D** = Dispatch; **I** = Installed Capacity.
 Static Data remains relatively constant over the lifetime of Bids but can be changed.
 General Data may be provided electronically or by mail, but requires a confirmation or Pre-Qualification process by the ISO.
 Some data will require substantiation by a test; actual data Bid may be subject to validation checking against Pre-Qualification data.
 Optional = Required only when providing or bidding to provide the associated service.

Issued by: William J. Museler, President

Effective: January 2, 2001

Issued on: January 16, 2001

Filed to comply with order of the Federal Energy Regulatory Commission, Docket No. ER99-4235-000, issued December 18, 2000.

Attachment D

Table D-1a

Data Requirements for Demand Side Resource for LBMP Bidders Resources

Data Item	Cat.	Bid Parameters	Variability	Comments
Company Name	G	--	Static Required	Parent Organization <u>organization</u> .
Generator Name/No.	G	--	Static Required	
Generator Unit Code/ID	G	--	Static Required	Unique code which identifies the Demand Side Resource to the ISO.
Bus	G	Bus No.	Static Required	Specific location of Demand Side Resource within the NYCA.
Submitted By	G	Name	May vary Required	Organization submitting Bid. Multiple organization can be authorized to submit Bids with the ISO accepting the most recent. A single organization must be specified to receive invoices from the ISO.
DMNC (Summer & Winter)	P/G	MW	Static Required	Specify maximum, megawatt curtailment <u>curtailment bid</u> .
Power Factor	P/G	MW/MVA	Static Optional	Values to be initialized pursuant to ISO requirements.
Installed Capacity Contracts	G	MW	May vary Required	Installed Capacity contracts in effect with <u>between Special Case Resources that are Demand Side Resources and</u> LSEs within the NYCA. The ISO may limit maximum and/or minimum amounts of Installed Capacity by location due to reliability Constraints.
<u>Normal Upper Operating Limit</u>	C/D	MW	May change <u>vary</u> Required by hour for Day-Ahead	Maximum output of a demand side resource <u>Demand Side Resource</u> that could be expected in any hour of the following operating day. The ISO must be informed of a limit change that results in less <u>capability</u> less <u>Capability</u> .
<u>Emergency Upper Operating Limit</u>	C/D	MW	May vary <u>Required by hour for Day-Ahead</u>	Maximum output that a Demand Side Resource expects to be able to reach during extraordinary conditions. <u>A Demand Side Resource's Emergency Upper Operating Limit may be no lower than its Normal Upper Operating Limit.</u>
Normal Response Rate (NRR)	P/C/D	MW/min.	May vary Required	Values to be initialized pursuant to ISO <u>To be provided as an expected response rate for RTD. Demand Side Resources may specify up to three NRRs. requirements. The minimum acceptable response rate is 1% of the quantity of Demand Reductions that the Demand Side Resource produces per minute.</u>
Regulation Response Rate (RRR)	P/C/D	MW/Min.	Same as <u>Optional</u> NRR	Values to be initialized pursuant to ISO requirements.
Emergency Response Rate (ERR)	P/C/D	MW/Min. or <u>Piecewise linear curve with MW Output as independent variable and MW/Min. as dependent variable</u>	Same as <u>Optional</u> NRR	Values to be initialized pursuant to ISO <u>To be provided as expected response for reserve pickups. A Demand Side Resource's ERR must be requirements greater than or equal to the capacity-weighted average of its NRRs.</u>
Reactive Power <u>Physical Minimum Demand Reduction Capability Limit</u>	P/G	Piecewise linear curve with MW as independent variable and +/- MVAr as dependent variable <u>MW</u>	Static <u>Optional</u> <u>Required</u>	Values to be initialized pursuant to ISO requirements.

Notes:

Demand Side Resource LBMP bidders are located within the NYCA.

Cat. = Data Categories: **G** = General; **P** = Pre-Qualification; **C** = Commitment; **B** = Balancing; **D** = Dispatch; **I** = Installed Capacity.

Static Data remains relatively constant over the lifetime of Bids but can be changed.

General Data may be provided electronically or by mail, but requires a confirmation or Pre-Qualification process by the ISO.

Some data will require substantiation by a test; actual data Bid may be subject to validation checking against Pre-Qualification data.

Optional = Required only when providing or bidding to provide the associated service.

Issued by: William J. Museler, President
 Issued on: April 4, 2001

Effective: May 1, 2001

Attachment D
Table D-2
Data Requirements for External Generators for ~~LBMP Bidders~~

Data Item	Cat.	Bid Parameters	Variability	Comments
Company Name	G	--	Static Required	Parent Organization.
Generator Name/No.	G	--	Static Required	
Generator Unit Code/ID	G	--	Static Required	Unique code which identifies the Generator to the ISO.
Submitted By	G	Name	May vary Required	Organization submitting Bid. Multiple organizations can be authorized to submit Bids with the ISO accepting the most recent. A single organization must be specified to receive invoices from the ISO.
Dependable Maximum Net Capability	P/G	MW	Static Required	Confirmed by test for units <u>Generators</u> with installed <u>Installed capacity</u> <u>Capacity</u> contracts.
Installed Capacity Contracts	P/G	MW	Variable (not within a Bid) Optional	Installed Capacity contracts in effect with LSEs within the NYCA. The ISO may limit maximum and/or minimum amounts of Installed Capacity by location due to reliability Constraints.
<u>Normal Upper Operating Limit</u>	<u>C/D</u>	<u>MW</u>	May change <u>vary</u> by hour for Day-Ahead Required	Maximum output of a unit <u>Generator</u> that could be expected in any hour of the following operating day. The ISO must be informed of a limit change that results in less capability <u>Capability</u> .
<u>Emergency Upper Operating Limit</u>	<u>C/D</u>	<u>MW</u>	<u>May vary Required by hour for Day-Ahead</u>	<u>Maximum output that a Generator's owner expects it can reach during extraordinary conditions. A Generator's Emergency Upper Operating Limit may be no lower than its Normal Upper Operating Limit.</u>
<u>Physical Minimum Generation Limit</u>	<u>P/G</u>	<u>MW</u>	<u>Static Required</u>	

Notes:

External Generators LBMP bidders are located outside the NYCA.

Cat. = Data Categories: **G** = General; **P** = Pre-Qualification; **C** = Commitment; **B** = Balancing; **D** = Dispatch; **I** = Installed Capacity.

Static Data remains relatively constant over the lifetime of Bids but can be changed.

General Data may be provided electronically or by mail, but requires a confirmation or Pre-Qualification process by the ISO.

Some data will require substantiation by a test; actual data Bid may be subject to validation checking against Pre-Qualification data.

Optional = Required only when providing or bidding to provide the associated service.

Issued by: William J. Museler, President

Effective: January 2, 2001

Issued on: January 16, 2001

Filed to comply with order of the Federal Energy Regulatory Commission, Docket No. ER99-4235-000, issued December 18, 2000.

Attachment D				
Table D-3				
Data Requirements for Generator Commitment Bids for LBMP Bidders				
Data Item	Cat.	Bid Parameters	Variability	Comments
Startup Time	C/B	Hours: Minutes or Piecewise linear curve with Hours Off-Line as independent variable and Hours to Start as dependent variable	May be changed for any Day-Ahead or Real-Time Commitment Required	Length of time needed to startup an off-line Generator, synchronize it to the power grid and stabilize at minimum.
Startup Bid Price	C/B	\$\$ to Start specified hourly or Piecewise linear curve with Hours Off-Line as an independent variable and \$ to Start as a dependent variable	May be changed hourly for any Day-Ahead Commitment. May only be lowered in the Real-Time Commitment in any hour in which the Generator has a Day-Ahead schedule. Required	
Minimum Run Time	C/B	Hours:Minutes	May be changed for any Day-Ahead Commitment, but may not be changed once a Generator is online. May be changed in Real-Time if the Generator is not currently online. is on-line Required	Duration of time that a Generator must run once started before it can subsequently be decommitted. Minimum Run Time cannot be honored past the end of the Dispatch Day. <u>The longest Minimum Run Time allowed in the Real-Time Market shall be one hour.</u>
Minimum Down Time	C/B	Hours:Minutes	May be changed for any Day-Ahead or Real-Time Commitment Required	Duration of time that a Generator must remain off-line following decommission before it can be re-started. <u>SCUC shall honor Minimum Down Time within a twenty four hour Dispatch Day. RTC will honor Minimum Down Times in the Real-Time Market unless the Generator has a Day-Ahead Schedule for any portion of the RTC optimization period.</u>
Maximum Number of Startups per Day	C/B	No	Static Required	<u>RTC will monitor but will not honor this parameter.</u>
Notes: Cat. = Data Categories: G = General; P = Pre-Qualification; B = Balancing; D = Dispatch; I = Installed Capacity. Static Data remains relatively constant over the lifetime of bids but can be changed.				

Issued by: William J. Museler, President
 Issued on: January 16, 2001

Effective: January 2, 2001

Filed to comply with order of the Federal Energy Regulatory Commission, Docket No. ER99-4235-000, issued December 18, 2000.

Attachment D
Table-D-3a

Data Requirements for Demand Side Resource Commitment Bids for LBMP Bidders

Data Item	Cat.	Bid Parameters	Variability	Comments
Startup Time	C/B	Hours: Minutes or Piecewise linear curve with Hours Off-Line as independent variable and Hours to Start as dependent variable	May be changed for any Day-Ahead or <u>Real-Time</u> Commitment Required	ISO will provide assumed value. <u>Length of time needed to respond to the ISO's signal to begin reducing demand.</u>
Startup Bid Price	C/B	\$ to Start or Piecewise linear curve with Hours Off-Line as independent variable and \$ to Start specified hourly as dependent variable	May be changed <u>hourly</u> for any Day-Ahead Commitment and, for any Real-Time Commitment in an hour in which the Demand Side Resource does not have a Day-Ahead schedule. Required	The Curtailment Initiation Cost should be entered here
Minimum Run Time	C/B	Hours:Minutes	May be changed for any Day-Ahead or <u>Real-Time</u> Commitment; may not be changed once unit Resource is on-line Required	Duration of time that the Demand Side Resource must reduce its demand once started before it can subsequently be decommitted. Minimum Run Time cannot be for more than 8 hours and cannot be honored past the end of the Dispatch Day. <u>The longest Minimum Run Time allowed in the Real-Time Market shall be one hour.</u>
Minimum Down Time	C/B	Hours:Minutes	May be changed for any Day-Ahead or <u>Real-Time</u> Commitment Required	Values to be initialized pursuant to ISO requirements <u>Duration of time that the Demand Side Resource must remain off-line following decommission before it can be re-started. SCUC shall honor Minimum Down Time within a twenty four hour Dispatch Day. RTC will honor Minimum Down Times in the Real-Time Market unless the Demand Side Resource has a Day-Ahead Schedule for any portion of RTC's optimization period.</u>
Maximum Number of Startups per Day	C/B	No	Static (but may be changed in Real-Time Bids) Required	<u>RTC will monitor but will not honor this parameter.</u>
Notes: Cat. = Data Categories: G = General; P = Pre-Qualification; B = Balancing; D = Dispatch; I = Installed Capacity. Static Data remains relatively constant over the lifetime of bids but can be changed.				

Issued by: William J. Museler, President
Issued on: April 4, 2001

Effective: May 1, 2001

Attachment D
Table D-4
Data Requirements for Generator Energy Bids

Data Item	Cat.	Bid Parameters	Variability	Comments
Minimum Generation Energy Block and Bid Price	C/B	MW and \$/MWh	May vary by hour,	Must be provided for commitment. GT Gas turbine units that fully load on startup can use this form of bid in lieu of a Dispatchable Energy Bid, but will set LBMP when economic.
Dispatchable Energy Bids	C/B	For Single Price Block Bids: No. of Blocks, steps, \$/MW/Block or For Piecewise-Linear Price Bids: Piecewise linear curve with MW Output as independent variable \$/MWh, and \$/MW/MWs of each step as dependent variable	May vary by hour,	Block bids would be separated by a narrow steep slope segment between each block. Bids may consist of up to eleven constant cost incremental Energy steps. Resulting bid "curves" must be monotonically increasing (possessing a positive slope at all points) for SCD. The cost of each step must exceed the cost of the preceding step.
Dispatch Bidding Status/Mode	C/B	On/Off/ISO-Committed Flexible, ISO-Committed Fixed, Self-Committed Flexible, or Self-Committed Fixed	May vary by hour, ISO-Committed Flexible or Self-Committed Flexible Resources that are scheduled Day-Ahead may not be ISO-Committed Fixed in real-time unless a physical operating problem makes it impossible for them to be flexible.	Indicates if a unit will be on or off dispatch in real-time. ISO-Committed Fixed Generators are eligible to receive a Day-Ahead schedule on request.
Notes: Cat. = Data Categories: G = General; P = Pre-Qualification; C = Commitment; B = Balancing; D = Dispatch; I = Installed Capacity.				

Issued by: William J. Museler, President

Effective: January 2, 2001

Issued on: January 16, 2001

Filed to comply with order of the Federal Energy Regulatory Commission, Docket No. ER99-4235-000, issued December 18, 2000.

Attachment D				
Table D-4a				
Data Requirements for Demand-Side Resource Reduction Bids				
Data Item	Cat.	Bid Parameters	Variability	Comments
Minimum Generation Energy Block and Bid Price	C/B	MW and \$/MW hour	May vary by hour	Enter demand side resource Demand Side Resources' minimum reduction and bid Bid price . Must be provided for commitment.
Dispatchable Energy Bids	C/B	For Single Price Block Bids: No. of Blocks steps, \$/MW/Block or For Piecewise Linear Price Bids: Piecewise linear curve with MW-Output as independent variable \$/MWh, and \$/MW MWs of each step as dependent variable	May vary by hour	Block bids would be separated by a narrow steep slope segment between each block Bids may consist of up to eleven constant cost incremental Energy steps. The cost of each step must exceed the cost of the preceding step. Resulting bid "curves" must be monotonically increasing (possessing a positive slope at all points) for-SCD.
Dispatch Bidding Status Mode	C/B	On/Off ISO-Committed Flexible	May vary by hour	N/A. All Demand Side Resources shall automatically be ISO-Committed Flexible.
Notes: Cat. = Data Categories: G = General; P = Pre-Qualification; C = Commitment; B = Balancing; D = Dispatch; I = Installed Capacity.				

Issued by: William J. Museler, President
Issued on: April 4, 2001

Effective: May 1, 2001

Attachment D
Table D-5
Data Requirements for Generator Regulation ~~(and Frequency Control)~~ Service Bids

Data Item	Cat.	Bid Parameters	Variability	Comments
Regulation Capacity Availability Bid	C/B	Table D-4 is required MW	May vary by hour Optional Required	Generator must be able to respond to AGC Base Point Signals from the ISO. The Regulation Capacity Availability Bid along with the submitted Regulation Response Rate (from Table E <u>D</u> -1) represent the maximum response range in MW and change Rate in MW/Min. LSEs engaged in Bilateral Transaction wishing to Self-Supply regulation must also state Supplier and Location.
Regulation Capacity Price Bid	C/B	\$/MW	May vary by hour Optional Required	

Notes:

Cat. = Data Categories: **G** = General; **P** = Pre-Qualification; **C** = Commitment; **B** = Balancing; **D** = Dispatch; **I** = Installed Capacity.
 Regulation Service Bids made for the Day-Ahead Market which are accepted are binding for the next 24 hour operating day.
 Regulation Service not scheduled for use by the ISO may be marketed by the bidder providing no other terms or forward contracts are violated.
 Unscheduled Regulation Service may be bid into the ~~BME (Hour Ahead)~~ Real-Time Market, and may have a different Bid price than the Day-Ahead Bid.
 Optional = Required only when providing or bidding to provide the associated service.

Issued by: William J. Museler, President
 Issued on: January 16, 2001

Effective: January 2, 2001

Filed to comply with order of the Federal Energy Regulatory Commission, Docket No. ER99-4235-000, issued December 18, 2000.

Attachment D
Table D-6
Data Requirements for Generator Operating Reserve Bids

Data Item	Cat.	Bid Parameters	Variability	Comments
Class A 10 Minute Spinning Reserve Energy and Availability Bid	C/B/D	Same as in Table D-44 is required Also, MW Available and Day-Ahead-only \$/MW Availability Price Bid	May Required Day-Ahead, may vary by hour hourly Optional Real-Time Availability Bids will not be accepted. All Generators accepted to provide Energy will be treated as offering Reserves at a price of \$0/MW.	Spinning Reserve is energy available in 10 minutes from a synchronized resource MW Available is not separately Bid but is a function of the Bidder's ERR and UOL, located within the NYCA that is otherwise not committed or dispatched to its Upper Operating Limit. The Energy must be available for at least 30 minutes. All Generators with this bid type may be dispatched down by SCD and will be paid Lost Opportunity Cost if this occurs. A Class A unit not scheduled at maximum Bid Capacity in the Day-Ahead Market is limited in the amount of Energy it may otherwise market in the Day-Ahead Market, such that its original Day-Ahead Energy schedule plus its Day-Ahead Spinning Reserve schedule is still available to the ISO. Bidding into Day-Ahead Energy Market may create a forward contract for providing Class A Spinning Reserve. Energy produced in place of providing Spinning Reserve will be paid Real-Time LBMP. If a Class A unit availability bid is accepted Day-Ahead, it will be paid the Day-Ahead Spinning Reserve Availability Clearing Price. If accepted for Real-Time, it will be paid the Real-Time Spinning Reserve Availability Clearing Price. An Emergency Response Rate (ERR) must be provided. If no Day-Ahead Availability price is bid, an Availability Bid of \$0/MW will be assigned.
Class B 10 Minute Non-Synchronized Spinning Reserve Availability Bid	C/B/D	MW Available and Day-Ahead only \$/MW Availability Price Bid	May vary by hour Required Day-Ahead, may vary hourly Real-Time Availability Bids will not be accepted. All Generators accepted to provide Energy will be treated as offering Reserves at a price of \$0/MW. Optional	Spinning Reserve is Energy available in 10 minutes from a synchronized resource located within the NYCA that is otherwise not operating at its Upper Operating Limit MW Available is not separately Bid but is a function of the Bidder's UOL. The Energy must be available for at least 30 minutes. A Class B unit is not committed or scheduled for LBMP Energy, but can bid an If no Day-Ahead Availability price is bid, an Availability for Spinning Reserve. If accepted Day-Ahead, it will be paid the Day-Ahead Spinning Reserve Availability Clearing Price. If accepted for Real-Time, it will be paid the Real-Time Spinning Reserve Availability Clearing Price. It will not be paid Lost Opportunity Cost. Any Energy produced will be paid Real-Time LBMP, but Class B units will not set LBMP Bid of An Emergency Response Rate (ERR) must be provided \$0/MW will be assigned.
Non-Synchronized 10 Minute Operating Reserve	C/B/D	MW Available and \$/MW Availability Price Bid	May vary by hour Optional	MW Bid must be available 10 minutes after requested. May be located External to NYCA provided the Inter-Control Area DNI Associated with this Resource can be changed in the required time. If accepted Day-Ahead, it will be paid the Day-Ahead Non-Synchronized 10 Minute Reserve Availability Clearing Price. If accepted for Real-Time, it will be paid the Real-Time Non-Synchronized 10 Minute Reserve Availability Clearing Price. Any Energy produced will be paid Real-Time LBMP.
30 Minute Operating Reserve Spinning or Non-Synchronized	C/B/D	MW Available and Day-Ahead only \$/MW Availability Price Bid	May vary by hour Required Day-Ahead, may vary hourly Real-Time Availability Bids will not be accepted. All	MW Bid must be available 30 minutes after requested. MW Available is not separately Bid but is a function of the Bidder's ERR if synchronized, and its UOL. May be located External to NYCA provided the Inter-Control Area DNI Associated with this Resource can be changed in the required time. If no Day-Ahead Availability price is bid, an Availability Bid of zero \$/MW will be assigned.

Attachment D
Table D-7
Data Requirements for Virtual Transaction Bids to Purchase Energy in the Day-Ahead Market

Data Item	Cat.	Bid Parameters	Variability	Comments
Company Name	G	--	Static	LSE, Energy Service Co. or other Transmission/Distribution Co. providing Load forecast.
Point of Withdrawal (Sink) Location	G	For Internal Loads: LBMP Zone or Zone and Bus or For External Loads: Control Area or Control Area and Proxy Bus	Static	
Submitted By	G	Name	May Vary	Organization submitting Bid.
Energy Forecast	C/B/D	MWh/hr	Variable by Hour	Total Estimate for Bid and non-Bid Load; ISO will rely on <u>its</u> own composite Load forecast as a reliability commitment to <u>insure</u> ensure that all Load is served. May be updated after DAM and/or Real Time to indicate adjusted Load served.
Energy Commit Bid	C/B/D	MW that will be committed for Day-Ahead Forward Contract	Variable by hour	Bidding is limited to the Day-Ahead Market.
Price Capped Energy Block Bids	C/B/D	No. of Blocks, MW/Block, and \$/MW/Block	Variable by hour	Bidding is limited to the Day-Ahead Market.

Notes:

Cat. = Data Categories: **G** = General; **P**= Pre-Qualification; **C** = Commitment; **B** = Balancing; **D**= Dispatch; **I** = Installed Capacity.
 Energy Bids made for the Day-Ahead Market which are accepted are binding for the next 24 hour operating day.

Attachment D
Table D-7.1
Data Requirements for Virtual Transaction Bids to Supply Energy

Data Item	Cat.	Bid Parameters	Variability	Comments
Company Name	G	--	Static	LSE, Energy Service Co. or other Transmission/Distribution Co. providing Load forecast.
Point of Injection (Source) Location	G	LBMP Zone	Static	
Submitted By	G	Name	May Vary	Organization submitting Bid.
Price Capped Energy Block Bids	C/B/D	No. of Blocks, MW/Block, and \$/MW/Block	Variable by hour	Bidding is limited to the Day-Ahead Market.

Notes:

Cat. = Data Categories: **G** = General; **P** = Pre-Qualification; **C** = Commitment; **B** = Balancing; **D** = Dispatch; **I** = Installed Capacity.
 Energy Bids made for the Day-Ahead Market which are accepted are binding for the next 24 hour operating day.

Issued by: William J. Museler, President
 Issued on: September 4, 2001

Effective: October 30, 2001

New York Independent System Operator, Inc.
 FERC Electric Tariff
 Original Volume No. 2
 Attachment D

Original Sheet No. 435

Attachment D
Table D-8

Data Requirements for Interruptible Load Spinning Reserve Bids

Data Item	Cat.	Bid Parameters	Variability	Comments
Interruptible Load for 10-Minute Spinning Reserve	C/B/D	MW Available, and \$/MW Availability Price Bid	May Bid Day Ahead	<p>Spinning Reserve is Energy available in 10 minutes from a synchronized Load (by definition, all Load being served is synchronized) located within the NYCA that is interruptible on demand.</p> <p>An interruptible Load spinning reserve Bid must include an Energy Load Bid equal to or greater than the interruptible Load Bid (i.e., it must be consuming Energy in order to provide spinning reserve in the form of a Load interruption); must be reflected to an ISO bus location; must interrupt full amount within 10 minutes; and must be able to be interrupted for at least 30 minutes.</p> <p>An interruptible Load is equivalent to Class B 10 Minute Spinning Reserve.</p> <p>An interruptible Load that is scheduled Day Ahead to provide Spinning Reserve will be paid the Day Ahead Spinning Reserve Availability Clearing Price. If scheduled to provide Spinning Reserve in real-time, it will be paid the Real-Time Spinning Reserve Availability Clearing Price.</p> <p>An interruptible Load providing Spinning Reserve must meet the requirements of the ISO including the ability to be monitored to measure interruptions.</p>
Interruptible Load for 30-Minute Reserve	C/B/D	MW Available, and \$/MW Availability Price Bid	May Bid Day Ahead	<p>30-Minute Reserve is Energy available in 30 minutes from a synchronized Load (by definition, all Load being served is synchronized) located within the NYCA that is interruptible on demand.</p> <p>An interruptible Load 30-minute reserve Bid must include an Energy Load Bid equal to or greater than the interruptible Load Bid (i.e., it must be consuming Energy in order to provide operating reserve in the form of a Load interruption); must be reflected to an ISO bus location; must interrupt full amount within 30 minutes.</p> <p>An interruptible Load that is scheduled Day Ahead to provide 30-minute Reserve will be paid the Day Ahead 30-minute Reserve Availability Clearing Price. If scheduled to provide 30-minute Reserve in real-time, it will be paid the Real-Time 30-minute Reserve Availability Clearing Price.</p> <p>An interruptible Load providing 30-minute Reserve must meet the requirements of the ISO including the ability to be monitored to measure interruptions.</p>

Notes:

- Cat. = Data Categories: **G** = General; **P** = Pre-Qualification; **C** = Commitment; **B** = Balancing; **D** = Dispatch; **I** = Installed Capacity.
- Operating Reserve Bids made for the Day-Ahead Market which are accepted are binding for the next 24 hour operating day.
- Operating Reserve not scheduled for use by the ISO may be marketed by the bidder providing no other terms or forward contracts are violated.
- Unscheduled Operating Reserve may be bid into the BME (Hour Ahead) Market, and may have a different Bid cost than the Day Ahead Bid.

Issued by: William J. Museler, President

Effective: January 2, 2001

Issued on: January 16, 2001

Filed to comply with order of the Federal Energy Regulatory Commission, Docket No. ER99-4235-000, issued December 18, 2000.

New York Independent System Operator, Inc.
FERC Electric Tariff
Original Volume No. 2

Original Sheets No. 436 through 439

Sheet Nos. 436 through 439 are reserved for future use.

Issued by: William J. Museler, President
Issued on: January 16, 2001

Effective: January 2, 2001

Filed to comply with order of the Federal Energy Regulatory Commission, Docket No. ER99-4235-000, issued
December 18, 2000.

Document comparison done by DeltaView on Thursday, October 09, 2003 15:22:17

Input:	
Document 1	pcdocs://washington/375560/1
Document 2	pcdocs://washington/377754/1
Rendering set	cathy

Legend:	
<u>Insertion</u>	
Deletion	
Moved from	
<u>Moved to</u>	
Format change	
Moved deletion	
Inserted cell	
Deleted cell	
Moved cell	
Split/Merged cell	
Padding cell	

Statistics:	
	Count
Insertions	165
Deletions	273
Moved from	0
Moved to	0
Format changed	0
Total changes	438